



h	c0	Em
[m]	Ø[m]	[lx]
1.0	0.18	15963
2.0	0.36	3991
3.0	0.54	1774
4.0	0.71	998
5.0	0.89	639

071 412 03 902 | stainless steel

in.ground 100 | square shaped design
in.ground luminaire
LED | 14 W 3000 K



- in.ground luminaire in.ground 100 square shaped design
- directional spotlight
- with recessing box of polyamid, fibreglass reinforced
- with LED 1200 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B50 (50.000h)
- SDCM < 2
- net luminous flux: 980 lm
- total load: 14 W
- luminous efficacy: 70,0 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 10 °
- with built in LED power unit, electronic, 220-240 V, 50/60 Hz
- power supply: supply cord, H07RN-F 3x1,5 mm², length: 500 mm
- housing of cast aluminium
- safety glass, clear
- with stainless steel cover frame
- length: 192 mm, width: 192 mm
- recessing depth: 221 mm
- load capacity 1000 kg or 3000 kg with separate installation housing of steel
- rotatable 360°, 0° - 30° tiltable
- weight: 3,8 kg
- protection rating: IP68 1m / 1h
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 40 ° C
- impact resistance class: IK10
- colour: stainless steel
- 071 412 03 902

- Overview of accessories on the following page / s

071 412 03 902

accessory**Optional accessories**

description accessory general	dimensions in mm	item number	pic.-No.
connection sleeve IP68 for ground recessed luminaire	ØxL: 26,5 x 116	071 212 00 000	01
moulded sleeve for connecting to an underground cable	LxWxH: 150 x 75 x 50	071 213 00 000	02
in-ground housing for ground recessed luminaire in.ground 100	LxWxH: 328 x 246 x 249	071 400 00 000	03

